

CS20 • CS24 CS26 RIBBED



CHOOSE YOUR OPTIONS


INSULATION	CS20	CS24	CS26
Foam/Insulate	Plain Steel/ T-Bond	Plain Steel/ T-Bond	Plain Steel/ T-Bond
R-Value	T-Bond: 7.0	T-Bond: 7.0	T-Bond: 7.0
U-Factor (Btu/hr/ft ² /F)	0.376	0.376	0.376
Thickness	2 inches	2 inches	2 inches
Maximum Width	40 ft 2 in	26 ft 2 in	16 ft 2 in
Exterior Steel	20 gauge	24 gauge	26 gauge
Warranty* Excludes Springs	10 years	10 years	25 years

COLORS



White

Sandtone



Coffee

Color Select™

*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.

*For full warranty details contact your Midland dealer




GLASS



Plain

Obscure


Frosted*



Gray

Bronze

Low E



Double Dark*

*Tempered only. All other glass is available in both tempered and untempered.

WINDOWS



24" x 5"



24" x 12"



32" x 14"

*Only available in 3-inch


TRACK MOUNTING



Reverse Angle Mounted Track
Continuous leg-in angle to attach to steel jambs




Angle Mounted Track
Continuous leg-out angle used on larger doors to attach to wood jambs



Bracket Mounted Track
To attach to wood jambs

TRACK CONFIGURATIONS



Standard Lift
For normal installations



Inclined Track
To follow pitch of roof



Hi-Lift
To put horizontal track as close to ceiling as possible



Vertical Lift
Full vertical rise where headroom is available



Low Headroom
For low-clearance installations

MIDLAND™
GARAGE DOOR MFG CO

midlandgaragedoor.com • 800.437.4056

YOUR LOCAL GARAGE DOOR PROFESSIONAL